SMARTPOMPE® | SMP130 SMP250 SMP450 SMP600

VOLUMETRIC PUMP WITH HELICAL LOBES

High technical quality Agri-food industry • product compliance Multifunctional





Designed and manufactured to provide the best pumping quality and to withstand the demanding conditions in the agri-food world. The **SMARTPOMPE®** is distinguished by its innovative helical lobes rotor technology and its wide range of potential applications.

4 models: flow rate from 15 to 600 hL/h

SMARTPOMPE® | SMP130

Flow rate from 15 to 130 hL/h

SMARTPOMPE® | SMP250

Flow rate from 25 to 250 hL/h

SMARTPOMPE® | SMP450

Flow rate from 30 to 450 hL/h

SMARTPOMPE® | **SMP600**

Flow rate from 100 to 600 hL/h



PRACTICAL

• On-board electronics:

speed variation, reverse direction, flow rate display, timer settings, servo control

 High frequency remote control: flow rate display, rechargeable

battery by induction, start/ forwards-reverse/ stop/ speed variation

- Draining, cleaning, easy maintenance
- Pump light and mobile
- Automatic motorised butterfly valve: guarantees no backflow when the pump is shut down

SELLING POINTS

- Stainless steel pump housing
- Lobes adapted to all types of products (sulphur-free and phthalates-free guaranteed)
- Conforms to EU machine regulations
- Mechanics 5 year warranty, excluding wear parts – On-board electronics 2 year warranty
- DN40, DN50, DN70 connection, or depending on your standards (Tri-clover, SMS, DIN, etc.)
- 10 meters of electric cable with a standard (European) plug
- The SMARTPOMPE® can work on ATEX areas (on request)



OPTIONS

• SMARTFLUX®:

Flowmeter adjustable, instantaneous reading

• Color touch screen 7 inches:



• SMART ELECTRONIC:

automatic barrel filling and racking

• SMART REGULATION:

adjustable regulation of the pump by pressure or by temperature

SMART DRIVE:

external control of the pump by other equipment

• BY GRAVITY:

free flow, with or without counting (SMARTFLUX®)

RUN-DRY SENSOR:

with adjustable timer



HIGH TECHNICAL QUALITY





- Pumping with an uninterrupted flow of liquid with no mixing or emulsion (does not require anti-pulsatory bottles and eliminates bacterial infections)
- Reduces up to 5 times the oxygen pick-up during transfers (significantly lower than other pumps)
- Resistance to high temperatures: enable sterilization up to 100 °C
- Suction vacuum capacity: 5 m
- Operating pressure: up to 6 bar

MULTIFUNCTIONAL



Racking - Transfer - Barrel filling - Filtration - Bottling

The **SMARTPOMPE®** pumps everything: juices, wine, beers, spirits, oil, must, juices at high temperature, cleaning products...

Manufacturer & customer service

PMH Equipements

ZA - 41 allée de la Croix des Hormes 69 250 Montanay - France Tél. +33 (0)4 72 21 83 00 Fax +33 (0)4 72 51 43 17 e-mail : info@pmh-vinicole.fr

PMHEQUIPEMENTS

FLUID CONTROL NINNOVATIVE SOLUTIONS